

Engineering Sketch Pad (ESP)



Training Session 10 Putting It All Together

John F. Dannenhoffer, III

jfdannen@syr.edu
Syracuse University

Bob Haines

haines@mit.edu
Massachusetts Institute of Technology

updated for v1.18

- During the design of an aircraft, various coupled models are needed
 - different disciplines
 - structures
 - controls
 - aerodynamics
 - ...
 - different fidelities
 - conceptual design
 - preliminary design
 - detailed design
- There needs to be communication between these models

- In order to support multi-fidelity and multi-disciplinary analyses, the CAPS program has been developed
 - funded by the AFRL
- CAPS uses geometries (and sensitivities) generated by ESP
- CAPS provides interfaces to many analysis programs, including:
 - aerodynamics (at various fidelities)
 - structures (at various fidelities)
 - ...
- There is a companion training course for CAPS that can be offered if there is sufficient interest


- One of the strengths of **ESP** is to be able to have multiple models of a single configuration
 - driven by a single set of Design Parameters
 - attributed so that “common” features could be linked together
- This capability has been used by the **CAPS** program
 - a set of “views” have been created, which can be used if the model is constructed and annotated in a consistent way
 - for AVL, SansLIP, SU2, Astros, ...
 - implemented as a series of UDCs

- Analysis of Simple Wing (`wing1`)
 - basic assumptions (orientation, ...)
 - required Bodys
 - required attributes (naming vs. meta-data)
- Analysis of wing with flaps (`wing2`)
 - required Bodys
 - required attributes (naming vs. meta-data)
- Analysis of wing structure `wing3`)
 - required Bodys
 - required attributes (naming vs. meta-data)
- Full aircraft model (`transport`)



wing1.csm

Isolated Wing: Outer Mold Line (OML) Only





Design Parameters for wing1

File can be found at `$ESP_ROOT/training/ESP/data/session10`

<code>wing:area</code>	10.0	wing area
<code>wing:aspect</code>	6.00	aspect ratio
<code>wing:taper</code>	0.60	taper ratio
<code>wing:sweep</code>	20.0	deg (of leading edge)
<code>wing:thick</code>	0.12	thickness ratio, frac of local chord
<code>wing:camber</code>	0.04	maximum camber, frac of local chord
<code>wing:washout</code>	5.00	deg (down at tip)
<code>wing:dihedral</code>	4.00	deg

- VIEW:Concept — conceptual design
- VIEW:VLM — vortex lattice method
- VIEW:CFDInviscid — inviscid CFD analysis
- VIEW:CFDViscous — viscous CFD analysis

- Configuration files defines the necessary Bodys
- Bodys are oriented such that:
 - x points out the tail
 - y points out the right wing
 - z points up

- Outer Mold Lines (OMLs) for each component
 - Fuse0ml (a SolidBody)
 - Wing0ml (a SolidBody)
 - Htail0ml (a SolidBody)
 - Vtail0ml (a SolidBody)

- Body
 - tagComp with value \$leftWing or \$rightWing
- Faces
 - tagComp with value \$leftWing or \$rightWing
 - tagType with value \$root, \$tip, \$upper, \$lower, or \$trailingEdge
- Edges
 - tagType with value \$root, \$leadingEdge (with supporting tagComp), or \$trailingEdge (with supporting tagComp)



Dissection of `wing1.csm` (1)

File can be found at `$ESP_ROOT/training/ESP/data/session10`

- Definition of VIEWS to be supported
- Definition of COMPONENTS that are defined
- Definition of Design Parameters
- Call to `capsHeader`
- Construction of `WingOml` (with attributes)
- Call to `capsViews`

```

# wing1
# written by John Dannenhoffer

# define the views
CFGPMTR  VIEW:Concept      1
CFGPMTR  VIEW:VLM          0
CFGPMTR  VIEW:CFDInviscid  0
CFGPMTR  VIEW:CFDViscous   0

# define components to be used
CFGPMTR  COMP:Wing         1

# Design Parameters for OML
DESPMTR  wing:area         10.0    # wing area
DESPMTR  wing:aspect       6.00    # aspect ratio
DESPMTR  wing:taper        0.60    # taper ratio
DESPMTR  wing:sweep        20.0    # deg (of leading edge)
DESPMTR  wing:thickr       0.12    # thickness ratio at root
DESPMTR  wing:camber       0.06    # camber ratio at root
DESPMTR  wing:thickt       0.16    # thickness ratio at tip
DESPMTR  wing:cambert      0.02    # camber ratio at tip
DESPMTR  wing:alphat       -5.00   # setting angle at tip
DESPMTR  wing:dihedral     4.00    # deg
DESPMTR  wing:xroot        0.00    # xloc at root LE
DESPMTR  wing:yroot        0.00    # yloc at root LE
DESPMTR  wing:zroot        0.00    # zloc at root LE

# Define length units of the geometry
ATTRIBUTE capsLength      $ft

```

```

# convert VIEW:* variables into make* variables
UDPRIM    $/capsHeader

# wing local variables
SET       wing:span      sqrt(wing:aspect*wing:area)
SET       wing:chordr    2*wing:area/wing:span/(1+wing:taper)
SET       wing:chordt    wing:chordr*wing:taper
SET       wing:ytip      -wing:span/2
SET       wing:xtip      -wing:ytip*tand(wing:sweep)
SET       wing:ztip      -wing:ytip*tand(wing:dihedral)
SET       wing:mac       sqrt(wing:area/wing:aspect)

# make wing OML
IFTHEN    makeWingOml EQ 1
  # lay out left wing
  MARK
  # root
  UDPRIM   naca      thickness  wing:thickr  camber  wing:camber  sharpte  SHARP_TE
  SCALE   wing:chordr
  ROTATEX 90 0 0

  # left tip
  UDPRIM   naca      thickness  wing:thickt  camber  wing:cambert  sharpte  SHARP_TE
  SCALE   wing:chordt
  ROTATEX 90 0 0
  ROTATEY wing:alphat 0          0
  TRANSLATE wing:xtip  wing:ytip  wing:ztip
RULE
  ATTRIBUTE tagComp $leftWing
SET       ruledBody @nbody

```

```
SELECT    FACE ruledBody 1
          ATTRIBUTE tagType $root
SELECT    FACE ruledBody 2
          ATTRIBUTE tagType $tip
SELECT    FACE ruledBody 3
          ATTRIBUTE tagType $upper
SELECT    FACE ruledBody 4
          ATTRIBUTE tagType $lower
SELECT    EDGE ruledBody 3 ruledBody 4 1
          ATTRIBUTE tagComp $leftWing
          ATTRIBUTE tagType $leadingEdge
IFTHEN    SHARP_TE EQ 0
          SELECT    FACE ruledBody 5
                ATTRIBUTE tagType $trailingEdge
ELSE
          SELECT    EDGE ruledBody 3 ruledBody 4 2
                ATTRIBUTE tagComp $leftWing
                ATTRIBUTE tagType $trailingEdge
ENDIF
```

```

# right wing too
STORE    LeftWing 0 1
RESTORE  LeftWing
  ATTRIBUTE tagComp $riteWing
  SELECT  EDGE  $tagType $leadingEdge
  IFTHEN  @iedge GT 0
    SELECT EDGE  $tagType $leadingEdge
    ATTRIBUTE tagComp $riteWing
  ENDIF
  SELECT  EDGE  $tagType $trailingEdge
  IFTHEN  @iedge GT 0
    SELECT EDGE  $tagType $trailingEdge
    ATTRIBUTE tagComp $riteWing
  ENDIF
  CATBEG  $edge_not_found
  CATEND
MIRROR  0  1  0
JOIN

SELECT  EDGE  ruledBody 3 ruledBody 3 1
  ATTRIBUTE tagType $root
SELECT  EDGE  ruledBody 4 ruledBody 4 1
  ATTRIBUTE tagType $root

STORE    Wing0ml
ENDIF

# now generate the needed views
UDPRIM  $/capsViews


END

```

<code>wing:hinge[i,1]</code>	deflection (degrees)
<code>wing:hinge[i,2]</code>	x/c at y -min end
<code>wing:hinge[i,3]</code>	$y/(b/2)$ at y -min end
<code>wing:hinge[i,4]</code>	z/t at y -min end
<code>wing:hinge[i,5]</code>	x/c at y -max end
<code>wing:hinge[i,6]</code>	$y/(b/2)$ at y -max end
<code>wing:hinge[i,7]</code>	z/t at y -max end
<code>wing:hinge[i,8]</code>	gap when cutting out for CFD
<code>wing:hinge[i,9]</code>	group (used to link controls in VLM)

- Outer Mold Lines (OMLs) for each component
 - FuseOml (a SolidBody)
 - WingOml (a SolidBody)
 - HtailOml (a SolidBody)
 - VtailOml (a SolidBody)
- Hinge lines for each control surface i on each component
 - WingHinge i (a WireBody)
 - HtailHinge i (a WireBody)
 - VtailHinge i (a WireBody)

- Body
 - (none required)
- Edges
 - `tagComp` with value `$wing`
 - `tagType` with value `$hinge`
 - `tagIndex` with value i
 - `deflect` with value equal to deflection angle (in degrees), positive according to right-hand rule
 - `xoverc1` with value equal to x/c at the y -min end
 - `xoverc2` with value equal to x/c at the y -max end
 - `gap` with value equal to gap size when cutting out control surface for CFD



File Tool StepThru Help

Up to date Undo

H C R B T + -

- Design Parameters
 - + VIEW: Viz
 - + COMP: Viz
 - + Wing: Viz
- + Local Variables
- + Branches
 - Display Viz
 - + Wing0ml Viz
 - + Body 44 Viz
 - + Body 45 Viz
 - Axis Viz
 - DisplayType
 - DisplayFilter


Parameter 'VIEW:CFDViscous[1,1]' has been changed to 1 =====> Re-build is needed <=====

Entire build complete, which generated 4 Body(s)

Parameter 'VIEW:Concept[1,1]' has been changed to 1 =====> Re-build is needed <=====

Parameter 'VIEW:CFDViscous[1,1]' has been changed to 0 =====> Re-build is needed <=====

Entire build complete, which generated 3 Body(s)



File | Tool | StepThru | Help

Up to date | Undo


H | T | R | B | T | + | -

- Design Parameters
 - + VIEW:
 - + COMP:
 - + Wing:
- + Local Variables
- + Branches
- Display
 - + Wing Via Grid
 - + Wing Via Grid
 - + FarField Via Grid
 - + Axes Via
 - DisplayType
 - DisplayFilter

www: .../data/99910610/VIEWBUILDSTRUCTURE.UIG

```

Parameter 'VIEW:Concept[1,1]' has been changed to 0 =====> Re-build is needed <=====
Parameter 'VIEW:CFDInviscid[1,1]' has been changed to 1 =====> Re-build is needed <=====
Entire build complete, which generated 2 Body(s)
Parameter 'COMP:Control[1,1]' has been changed to 1 =====> Re-build is needed <=====
Entire build complete, which generated 2 Body(s)
  
```



File | Tool | StepThru | Help

Up to date | Undo

H | T | R | B | T | + | -

- Design Parameters
 - + VIEW:
 - + COMP:
 - + Local Variables
 - + Branches
 - Display
 - + Wing
 - + WingControl_1
 - + WingControl_2
 - + Farfield
 - Axis
 - DisplayType
 - DisplayFilter

Parameter 'COMP:Control[1,1]' has been changed to 1 =====> Re-build is needed <=====

Entire build complete, which generated 2 Body(s)

Parameter 'VIEW:CFDInviscid[1,1]' has been changed to 0 =====> Re-build is needed <=====

Parameter 'VIEW:CFDViscous[1,1]' has been changed to 1 =====> Re-build is needed <=====

Entire build complete, which generated 4 Body(s)



Dissection of `wing2.csm` (1)

File can be found at `$ESP_ROOT/training/ESP/data/session10`

- Definition of `VIEW`s to be supported
- Definition of `COMPONENT`s that are defined
- Definition of Design Parameters
- Call to `capsHeader`
- Construction of `WingOml` (with attributes)
- Construction of `WingHinges` (with attributes)
- Call to `capsViews`

```

# wing2
# written by John Dannenhoffer

# define the views
CFGPMTR  VIEW:Concept      1
CFGPMTR  VIEW:VLM          0
CFGPMTR  VIEW:CFDInviscid  0
CFGPMTR  VIEW:CFDViscous   0

# define components to be used
CFGPMTR  COMP:Wing         1
CFGPMTR  COMP:Control      0

# Design Parameters for OML
DESPMTR  wing:area         10.0  # wing area
DESPMTR  wing:aspect       6.00  # aspect ratio
DESPMTR  wing:taper        0.60  # taper ratio
DESPMTR  wing:sweep        20.0  # deg (of leading edge)
DESPMTR  wing:thickr       0.12  # thickness ratio at root
DESPMTR  wing:cambrer      0.06  # camber ratio at root
DESPMTR  wing:thickt       0.16  # thickness ratio at tip
DESPMTR  wing:cambert      0.02  # camber ratio at tip
DESPMTR  wing:alphat       -5.00 # setting angle at tip
DESPMTR  wing:dihedral     4.00  # deg
DESPMTR  wing:xroot        0.00  # xloc at root LE
DESPMTR  wing:yroot        0.00  # yloc at root LE
DESPMTR  wing:zroot        0.00  # zloc at root LE

```



Dissection of wing2.csm (3)

```
# Design Parameters for controls
DIMENSION wing:hinge      2 9 1
#                          theta  ymin                    ymax          gap  grp
DESPMTR  wing:hinge      "-10.0; 0.75; -0.90; 0.50; 0.75; -0.50; 0.50; 0.10; 1; \ left aileron
                          +10.0; 0.75; 0.50; 0.50; 0.75; 0.90; 0.50; 0.10; 2" # rite aileron

# Define length units of the geometry
ATTRIBUTE capsLength      $ft

# convert VIEW:* variables into make* variables
UDPRIM    $/capsHeader

# wing local variables
SET      wing:span      sqrt(wing:aspect*wing:area)
SET      wing:chordr    2*wing:area/wing:span/(1+wing:taper)
SET      wing:chordt    wing:chordr*wing:taper
SET      wing:ytip      -wing:span/2
SET      wing:xtip      -wing:ytip*tand(wing:sweep)
SET      wing:ztip      -wing:ytip*tand(wing:dihedral)
SET      wing:mac       sqrt(wing:area/wing:aspect)
```

```

# make wing OML
IFTHEN    makeWingOml EQ 1
  # lay out left wing
  MARK
    # root
    UDPRIM    naca      thickness  wing:thickr  camber  wing:cambrerr  sharpte  SHARP_TE
    SCALE     wing:chordr
    ROTATEX   90  0  0

    # left tip
    UDPRIM    naca      thickness  wing:thickt  camber  wing:cambert  sharpte  SHARP_TE
    SCALE     wing:chordt
    ROTATEX   90  0  0
    ROTATEY   wing:alpat  0          0
    TRANSLATE wing:xtip   wing:ytip   wing:ztip

  RULE
    ATTRIBUTE tagComp $leftWing
  SET      ruledBody @nbody

  SELECT   FACE ruledBody 1
    ATTRIBUTE tagType $root
  SELECT   FACE ruledBody 2
    ATTRIBUTE tagType $tip
  SELECT   FACE ruledBody 3
    ATTRIBUTE tagType $upper
  SELECT   FACE ruledBody 4
    ATTRIBUTE tagType $lower
  SELECT   EDGE ruledBody 3 ruledBody 4 1
    ATTRIBUTE tagComp $leftWing
    ATTRIBUTE tagType $leadingEdge

```



Dissection of wing2.csm (5)

```
IFTHEN    SHARP_TE EQ 0
  SELECT   FACE    ruledBody 5
           ATTRIBUTE tagType $trailingEdge
ELSE
  SELECT   EDGE    ruledBody 3 ruledBody 4 2
           ATTRIBUTE tagComp $leftWing
           ATTRIBUTE tagType $trailingEdge
ENDIF

# right wing too
STORE     LeftWing 0 1
RESTORE   LeftWing
  ATTRIBUTE tagComp $riteWing
  SELECT   EDGE    $tagType $leadingEdge
  IFTHEN   @iedge GT 0
    SELECT EDGE    $tagType $leadingEdge
    ATTRIBUTE tagComp $riteWing
  ENDIF
  SELECT   EDGE    $tagType $trailingEdge
  IFTHEN   @iedge GT 0
    SELECT EDGE    $tagType $trailingEdge
    ATTRIBUTE tagComp $riteWing
  ENDIF
  CATBEG   $edge_not_found
  CATEND
MIRROR    0    1    0
JOIN
```

```

SELECT   EDGE   ruledBody 3 ruledBody 3 1
          ATTRIBUTE tagType $root
SELECT   EDGE   ruledBody 4 ruledBody 4 1
          ATTRIBUTE tagType $root

STORE    WingOml

ENDIF

# make wing hinge lines
IFTHEN   makeWingOml EQ 1 AND makeWingHinge EQ 1
  PATBEG   ihinge wing:hinge.nrow
  SET      y_ibd   wing:hinge[ihinge,3]*(-wing:ytip)
  BOX      -1000 y_ibd -1000 2000 0 2000
  RESTORE  WingOml
  INTERSECT
  SET      x_ibd   @xmin+wing:hinge[ihinge,2]*(@xmax-@xmin)
  STORE    .
  BOX      x_ibd y_ibd -1000 0 0 2000
  RESTORE  WingOml
  INTERSECT
  SET      z_ibd   @zmin+wing:hinge[ihinge,4]*(@zmax-@zmin)
  STORE    .

```

```


SET      y_obd   wing:hinge[ihinge,6]*(-wing:ytip)
BOX      -1000 y_obd -1000 2000 0 2000
RESTORE  Wing0m1
INTERSECT
SET      x_obd   @xmin+wing:hinge[ihinge,5]*(@xmax-@xmin)
STORE    .
BOX      x_obd y_obd -1000 0 0 2000
RESTORE  Wing0m1
INTERSECT
SET      z_obd   @zmin+wing:hinge[ihinge,7]*(@zmax-@zmin)
STORE    .

SKBEG    x_ibd y_ibd z_ibd
          LINSEG x_obd y_obd z_obd
SKEND
SELECT   EDGE 1
          ATTRIBUTE tagComp $wing
          ATTRIBUTE tagType $hinge
          ATTRIBUTE tagIndex !val2str(wing:hinge[ihinge,9],0)
          ATTRIBUTE deflect wing:hinge[ihinge,1]
          ATTRIBUTE xoverc1 wing:hinge[ihinge,2]
          ATTRIBUTE xoverc2 wing:hinge[ihinge,5]
          ATTRIBUTE gap wing:hinge[ihinge,8]
          ATTRIBUTE compIndex !val2str(ihinge,0)
STORE    WingHinge ihinge
PATEND
ENDIF

# now generate the needed views
UDPRIM   $/capsViews

END

```





New Design Parameters for wing3

wing:spar1	0.20	location of fwrdr spar
wing:spar2	0.70	location of rwrdr spar
wing:nrib	3.00	number of ribs per wing

- VIEW:Concept — conceptual design
- VIEW:Structure — built-up element model

- Outer Mold Lines (OMLs) for each component
 - FuseOml (a SolidBody)
 - WingOml (a SolidBody)
 - HtailOml (a SolidBody)
 - VtailOml (a SolidBody)
- Waffle for each component
 - FuseWaffle (a SheetBody) — not yet supported
 - WingWaffle (a SheetBody)
 - HtailWaffle (a SheetBody) — not yet supported
 - VtailWaffle (a SheetBody) — not yet supported



Required Attributes of WingWaffle

- Body
 - (none required)
- Faces
 - `tagComp` with value `$leftwing`, `$riteWing`, or `$wing` (if on symmetry plane)
 - `tagType` with value `$spar` or `$rib`
 - `tagIndex` with different value for each spar and rib

```

# wing3
# written by John Dannenhoffer

# define the views
CFGPMTR  VIEW:Concept      1
CFGPMTR  VIEW:VLM          0
CFGPMTR  VIEW:CFDInviscid  0
CFGPMTR  VIEW:CFDViscous  0
CFGPMTR  VIEW:OmlStructure 0
CFGPMTR  VIEW:ClampedStructure 0
CFGPMTR  VIEW:SupportStructure 0
CFGPMTR  VIEW:BoxStructure  0

# define components to be used
CFGPMTR  COMP:Wing        1

# Design Parameters for OML
DESPMTR  wing:area        10.0    # wing area
DESPMTR  wing:aspect      6.00    # aspect ratio
DESPMTR  wing:taper       0.60    # taper ratio
DESPMTR  wing:sweep       20.0    # deg (of leading edge)
DESPMTR  wing:thickr      0.12    # thickness ratio at root
DESPMTR  wing:camber      0.06    # camber ratio at root
DESPMTR  wing:thickt      0.16    # thickness ratio at tip
DESPMTR  wing:cambert     0.02    # camber ratio at tip
DESPMTR  wing:alphanat    -5.00   # setting angle at tip
DESPMTR  wing:dihedral    4.00    # deg
DESPMTR  wing:xroot       0.00    # xloc at root LE
DESPMTR  wing:yroot       0.00    # yloc at root LE
DESPMTR  wing:zroot       0.00    # zloc at root LE

```

```
# Design Parameters for structure
DESPMTR  wing:spar1  0.20      # location of fwd spar
DESPMTR  wing:spar2  0.70      # location of rwr spar
CFGPMTR  wing:nrib   3.00      # number of ribs per wing

# Define length units of the geometry
ATTRIBUTE capsLength $ft

# convert VIEW:* variables into make* variables
UDPRIM   $/capsHeader

# wing local variables
SET      wing:span sqrt(wing:aspect*wing:area)
SET      wing:chordr 2*wing:area/wing:span/(1+wing:taper)
SET      wing:chordt wing:chordr*wing:taper
SET      wing:ytip   -wing:span/2
SET      wing:xtip   -wing:ytip*tand(wing:sweep)
SET      wing:ztip   -wing:ytip*tand(wing:dihedral)
SET      wing:mac     sqrt(wing:area/wing:aspect)
```

```

# make wing OML
IFTHEN    makeWingOml EQ 1
    # lay out left wing
    MARK
        # root
        UDPRIM    naca      thickness wing:thickr   camber   wing:camberr   sharpte SHARP_TE
        SCALE     wing:chordr
        ROTATEX   90 0 0

        # left tip
        UDPRIM    naca      thickness wing:thickt   camber   wing:cambert   sharpte SHARP_TE
        SCALE     wing:chordt
        ROTATEX   90 0 0
        ROTATEY   wing:alhat 0           0
        TRANSLATE wing:xtip   wing:ytip   wing:ztip

RULE
    ATTRIBUTE tagComp $leftWing
SET      ruledBody @nbody

SELECT   FACE ruledBody 1
    ATTRIBUTE tagType $root
SELECT   FACE ruledBody 2
    ATTRIBUTE tagType $tip
    ATTRIBUTE tagIndex $1
SELECT   FACE ruledBody 3
    ATTRIBUTE tagType $upper
SELECT   FACE ruledBody 4
    ATTRIBUTE tagType $lower

```

```
SELECT    EDGE    ruledBody 3 ruledBody 4 1
  ATTRIBUTE tagComp $leftWing
  ATTRIBUTE tagType $leadingEdge
IFTHEN    SHARP_TE EQ 0
  SELECT    FACE    ruledBody 5
    ATTRIBUTE tagType $trailingEdge
ELSE
  SELECT    EDGE    ruledBody 3 ruledBody 4 2
    ATTRIBUTE tagComp $leftWing
    ATTRIBUTE tagType $trailingEdge
ENDIF

# right wing too
STORE    LeftWing 0 1
RESTORE  LeftWing
  ATTRIBUTE tagComp $riteWing
  SELECT    FACE    $tagType $tip
  ATTRIBUTE tagIndex $2
  SELECT    EDGE    $tagType $leadingEdge
  IFTHEN    @iedge GT 0
    SELECT EDGE    $tagType $leadingEdge
      ATTRIBUTE tagComp $riteWing
  ENDIF
  SELECT    EDGE    $tagType $trailingEdge
  IFTHEN    @iedge GT 0
    SELECT EDGE    $tagType $trailingEdge
      ATTRIBUTE tagComp $riteWing
  ENDIF
CATBEG    $edge_not_found
CATEND

MIRROR    0    1    0
JOIN
```



Dissection of wing3.csm (5)

```
SELECT  EDGE  ruledBody 3 ruledBody 3 1
        ATTRIBUTE tagType $root
SELECT  EDGE  ruledBody 4 ruledBody 4 1
        ATTRIBUTE tagType $root

STORE   WingOml
ENDIF

# make wing waffle
IFTHEN  makeWingWaffle EQ 1
    RESTORE WingOml
    SET   xmin      @xmin-0.1
    SET   xmax      @xmax+0.1
    SET   ymin      0
    SET   ymax      @ymax+0.1
    SET   zmin      @zmin-0.1
    SET   zmax      @zmax+0.1
    STORE .

UDPARG  waffle     depth wing:nrib    # ensures rebuild
UDPARG  waffle     depth wing:spar1
UDPARG  waffle     depth wing:spar2
UDPARG  waffle     depth zmax-zmin   filename <<
```

```

# construction lines for spars
CPOINT A   AT           0+wing:spar1*wing:chordr  0
CPOINT B   AT   wing:xtip+wing:spar1*wing:chordt -wing:ytip
CPOINT C   AT           0+wing:spar2*wing:chordr  0
CPOINT D   AT   wing:xtip+wing:spar2*wing:chordt -wing:ytip

CLINE AB    A   B
CLINE CD    C   D

# rite spars
POINT E   ON  AB   YLOC  ymin
POINT F   ON  AB   YLOC  ymax
LINE  EF   E   F   tagComp=riteWing  tagType=spar  tagIndex=1

POINT G   ON  CD   YLOC  ymin
POINT H   ON  CD   YLOC  ymax
LINE  GH   G   H   tagComp=riteWing  tagType=spar  tagIndex=2

# rite ribs
PATBEG  irib  wing:nrib
      CPOINT I   AT  xmin  -wing:ytip*irib/(wing:nrib+1)
      CPOINT J   AT  xmax  y@I
      LINE   .   I   J   tagComp=riteWing  tagType=rib   tagIndex=!val2str(irib,0)
PATEND

```

```

# root rib
CPOINT I AT xmin 0
CPOINT J AT xmax y@I
LINE . I J tagComp=rootWing tagType=rib tagIndex=0

# left spars
POINT E AT x@E -y@E
POINT F AT x@F -y@F
LINE FE F E tagComp=leftWing tagType=spar tagIndex=1

POINT G AT x@G -y@G
POINT H AT x@H -y@H
LINE HG H G tagComp=leftWing tagType=spar tagIndex=2

# left ribs
PATBEG irib wing:nrib
  CPOINT I AT xmin wing:ytip*irib/(wing:nrib+1)
  CPOINT J AT xmax y@I
  LINE . I J tagComp=leftWing tagType=rib tagIndex=!val2str(irib,0)
PATEND

>>
  TRANSLATE 0 0 zmin
  STORE WingWaffle
ENDIF

# now generate the needed views
UDPRIM $/capsViews

END

```



Full Transport Configuration

File found at `$ESP_ROOT/training/ESP/data/session10`

- Design Parameters associated with fuselage and tail
 - similar to wing
- Construction of fuselage and tail
 - similar to wing



The screenshot displays the ESP Engineering Sketch Pad interface. The main window shows a 3D model of an aircraft with a cutaway view of the wing structure. The left sidebar contains a tree view with the following items:

- Design Parameters
- Local Variables
- Branches
- Display
- FuseOml
- WingOml
- WingWaffle
- WingHinge_1
- WingHinge_2
- WingHinge_3
- WingHinge_4
- WingHinge_5
- WingHinge_6
- HtailOml
- HtailHinge_1
- HtailHinge_2
- VtailOml
- VtailHinge_1
- Axes
- Display Type
- Display Filter

The status bar at the bottom of the window displays the following text:

```
ESP has been initialized and is attached to 'serveCRM'  
"../data/caspeExamples/transport.csm" has been loaded
```

- ESP is a powerful geometry-generating system that was designed for the analysis of complex configurations
 - supports multiple linked models
 - supports persistent attribution
 - provides sensitivities
 - can easily be coupled with other systems
- For CAPS, a set of “views” were defined; but these are only an example
- Each organization will want to develop a set of rules and conventions that are consistent with the rest of the organization’s design systems

- ESP is freely available for download from `acd1.mit.edu/ESP`
- Based upon user requests, new and improved features are added continually
- Send bug reports to `jfdannen@syr.edu` or `haimes@mit.edu`
- Also send success stories to `jfdannen@syr.edu` or `haimes@mit.edu`

- Thank you for attending; send comments about the course to `jfdannen@syr.edu` or `haimes@mit.edu`